

FARROW SYSTEM 400HP™ Mobile Cleaning Unit

THE FARROW
system®
Patented Method for Removing Surface Coatings

Cleans everything. Period.

Fight corrosion and remove tough protective coatings anywhere with the Farrow 400HP™ high volume cleaning machine. It has a powerful Kaeser 400CFM air compressor mounted to a fully galvanized trailer frame featuring tandem wheels and standard surge brakes for easy handling. Simply tow it to your jobsite, and with the 130 gallon on board water tank, you are ready to get to work! The unit comes with a 50 foot hose, and will reach up to 300 feet by using extension hoses! The Farrow 400HP™ is a heavy duty machine engineered to deliver many years of dependable operation. It will deliver efficient, safe, and low cost large scale cleaning in maritime, industrial, and infra-structure applications.

MADE IN USA




1-888-FARROW-8
www.farrowssystem.com



FARROW SYSTEM 400HP[™]



The 100% stainless steel control cabinet is super durable and sealed against the elements. It houses the dosing regulators, controls, valves, and gauges that monitor the system performance. Intuitive controls are easy to use, reducing training time required to get consistent results.



Heat is added to the process simply and reliably with a high-efficiency heat exchanger. It transfers heat from the compressor oil to the water, heating the pressurized pot. All hot elements are safely located behind the lockable side covers.



Compressed air is used to pump water for the process from the on board water tank. This high reliability WIWA pump delivers consistent pressure, is efficient, and is built to give you years of trouble-free service.



Safety is one of The Farrow System's[®] major goals. Our Farrow System 400HP[®] mobile units have tandem axles which deliver superior load distribution and tracking during towing. Hydraulic surge brakes are standard on each wheel, and electric trailer brakes can be ordered as an option.



The pressure pot is a key component of the Farrow System[®]. Specifically sized for the output of the machine, each pot complies with ASME vessel code regulations Section VIII, Division One. Each pot is powder coated inside and out to assure maximum reliability and longevity in the field.



SPECIFICATIONS

General	
Dimensions	173"L x 84"W x 73"H
Weight	5,489 Lbs. Dry
Pot Diameter	24 In.
Trailer Water Capacity	130 Gal.
Pot Media Capacity	400lb. - 8 Bags Farrow Green Clean [®]
Blasting Pressure	Up To 125 PSI
Hose Length	50 Ft. (Up to 300 Ft. optional)
Available Accessories	Hose Extension, Blast Nozzle & Holder, Handle Assembly
Warranty*	Complete Machine for 1 Year From Original Purchase Date; Engine & Compressor Are Supported By The Manufacturer's Warranty.*
Engine	
Type	Diesel Tier 3
Model	Kubota V3800
Power	90 HP @ 2600 RPM
Oil System	3.4 Gal. Capacity, Full Pressurized Lubrication, Spin-on Filter
Battery	12VDC
Idle Control	Fully Automatic Low Idle System
Fuel Tank Capacity	40 Gal. Rust Proof Tank
Compressor	
Type	Direct Drive Twin Screw
Rated Delivery	400 CFM
Operating Pressure	145 PSI
Lubrication System	Pressurized Lubrication, Spin-on Cartridge Filter, Thermostatically Controlled Oil-to-Air Cooler.
Pressure Relief	1/2" Pop-off Safety Valve
Specs Based On	Kaeser M100 HP
*Please see complete warranty for details.	
** Specifications subject to change without notice.	

Your local authorized Farrow System[®] dealer: